



**ZASTAVA
KAMIONI**



New Turbo Rival 4x2



ZASTAVA KAMIONI

ZASTAVA KAMIONI d.o.o, Kragujevac

- u restrukturiranju

Kosovska 4 · 34000 Kragujevac · Republika Srbija

tel: ++381 34 336 160 · fax: ++381 34 335 319



e-mail: prodaja@zastava-kamioni.co.rs

www.zastava-kamioni.co.rs



New Turbo Rival 4x2

TIP I VRSTA MOTORA	EURO 3	SOFIM 8140.43S - Dizel, četiri takta sa direktnim ubrizgavanjem goriva, (COMMON RAIL)
RADNA ZAPREMINA (cm ³)		2800
MAKSIMALNA SNAGA PRI 3600 o/min.		92 kW / 125 KS
MAKSIMALNI OBRтни MOMENT PRI 1800 o/min.		290 Nm
VRSTA HLADENJA		VOĐENO
SPOJNICA		Suva sa jednim diskom i mehaničkom komandom od 10 1/2"
MENJAČ		IVECO 2826.5 Mehanički sa 5 sinhronizovanih stepena prenosa napred i hodom nazad
KOČNICA		Hidraulična servokočnica sa ABS-om, depresorom i dva nezavisna kruga, napred disk, pozadi doboš kočnica
UPRAVLJAČ		Hidraulički sa servo dejstvom



TEHNIČKI PODACI	ŠASIJA SA KABINOM						ŠASIJA SA PRODUŽENOM KABINOM						KAMION SA PRODUŽENOM KABINOM						FURGON SA PODIGNUTIM KROVOM						KOMBI				MINIBUS			
	6+1		8+1		KAMION		6+1		8+1		FURGON		30.12H		13+1		16+1		19+1													
modeli	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	40.12H	49.12H	35.12H	40.12H	49.12H	35.12H	40.12H	49.12H	30.12H	40.12H	40.12H	49.12H						
OSNO RASTOJANJE (mm)	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	3310	2800									
DUŽINA VOZILA (mm)	5740	5740	5740	5740	5740	5740	5740	5740	5780	5780	5780	5915	5915	5915	5940	5940	5965	5965	5965	5965	5965	5965	4815	4815	4815	5965	5965					
ŠIRINA VOZILA (mm)	2000		2000		2000		2140		2140		2140		2140		2000		2000		2000		2000		2000	2000		2000						
VISINA VOZILA (mm)	2085		2085		2085		2085		2085		2085		2085		2250		2250		2250		2250		2255	2255		2700						
UNUTRAŠNJA DUŽINA TOV. SANDUKA / PROSTORA (mm)									3493	3493	3493	2801	2801	2801	2140	2140	3613	3613	3613	3613	3613	3613										
UN.ŠIRINA TOV. SANDUKA (mm)									2073	2073	2073	2073	2073	2073	2073	2073	1820	1820	1820	1820	1820	1820					1820					
VISINA TOV. SANDUKA (mm)									400	400	400	400	400	400	400	400	1512	1512	1512	1512	1512	1512										
ZAPREMINA TOVARNOG PROSTORA (m ³)																	6.8	6.8	6.8	6.8	6.8	6.8										
VIS. PODA VOZILA OD TLA (mm)	825		825		825		825		1050		1050		1050		790		790		790		790		750	750		800						
KORISNA NOSIVOST (kg)	1580	2280	3040	1450	2150	2910	2000	2760	1350	2050	2790	1220	1920	2690	1800	2560	1440	1900	2640	1270	1920	2660	8 put. + 400	13 put. + 545	16 put. + 250	19 put. + 450						
DOZVOLJENA UKUPNA MASA (kg)	3500	4200	5000	3500	4200	5000	4200	5000	3500	4200	5000	3500	4200	5000	4200	5000	3500	4200	5000	3500	4200	5000	3170	4200	4200	5000	5000					
PNEUMATICI	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	215/75 R16	185/75 R16	185/75 R16	215/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16	185/75 R16				
MAKSIMALNA BRZINA (km/h)	117	117	105	117	117	105	117	105	117	117	105	117	117	105	117	105	117	105	117	105	117	105	117	117	117	117	117	117				
ZAPREMINA REZ. ZA GORIVO (l)	70		70		70		70		70		70		70		70		70		70		70		70	70		70						

U OKVIRU POLITIKE UNAPREDJENJA PROIZVODA ZASTAVA KAMIONI MOGU BEZ PREDHODNOG OBAVEŠTENJA IZMENITI TEHNIČKE KARAKTERISTIKE.